



**SC 405**  
(With LCD & Keypad)  
129mm x 100mm x 40mm

## ➔ Proximity T&A System with Access Control

Card Capacity : 30,000  
Transaction Storage : 50,000  
Card Reader : Yes  
CPU : 32 bit High End Microprocessor  
FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$   
Identification Speed :  $\leq 0.1$  sec  
Display : Black & White  
Keypad : 4 x 4 Keypads  
LED Indicator : Green/Red  
Schedule Bell/Speaker : Mini Speaker  
Communication : TCP/IP,USB,RS485  
Power Supply : 12V DC, 2amps / 3amps  
Operating Temperature : 0°C to 45°C  
Operating Humidity : 20% -80%  
Dimension : 143 x 95.5 x39.5mm  
**Access Control** : Wiegand : In & Out  
Relay : Inbuilt relay to communicate with Locks,  
Alarms & Door Sensors

Support Fire Alarm : Yes / Door Sensor : Yes  
Anti Passback : Yes / Door Bell : Yes  
Support exit reader : KR 500E / Exit Button /  
101 HE,50 time zones, 5 groups, 10 time combinations  
Battery : No / Card Readers : Yes  
Communication : No  
Printer : No

### **Compatibility :**

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

### **Compatible Software & SDK :**

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications