



VF380

➔ Multibiometric Identification Time Attendance & Access Control System

Face Capacity : 800
 Card Capacity : 10,000
 Transaction storage : 1,00,000 logs
 Card Reader : Yes
 Image Sensor : Special Sterio Dual Sensor
 FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
 Identification Speed : ≤ 1 Sec
 Algorithm Ver : NA
 Display : 3" TFT Screen
 Schedule Bell/Speaker : Mini Speaker
 Communication : TCP/IP , USB- Host
 Camera : High Resolution Infrared Camera
 Standard Features : Automatic Status Switch,
 Self Service Query Work code
 Power Supply : 12V DC, 1.5 Amps
 Operating Temperature : 0°C to 45°C
 Operating Humidity : 20% -80%
 Dimension : 104.70 x 160.00 x 36.00 mm

Access Control :

Wiegand : No
 Relay : 12 V
 Support Fire Alarm : Yes / Door Sensor ; Yes
 Anti Passback : No / Door Bell : Yes
 Support exit reader : No
 Battery : No / Card Readers : Yes
 Communication : No
 Printer : No

Compatibility :

- Door Sensor, EM Lock

Compatible Software & SDK :

- Smart office suite desktop and web
 - Etime track lite desktop & web
 - SDK for desktop applications
 - Web based Device Manager/ePush server using
 Push data. Helps developers & integrators
 - Supports 3rd Party Payroll/HRMS/ERP
 and Other applications